

# SAFETY DATA SHEET Permabond ET5145B

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name Permabond ET5145B

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses**Two-component, epoxy-based adhesive.

# 1.3. Details of the supplier of the safety data sheet

**Supplier** Permabond Engineering Adhesives Ltd.

Wessex Way Colden Common Winchester

Hampshire SO21 1WP United Kingdom

Tel: +44 (0)1962 711 661 Fax: +44 (0)1962 711 662 info.europe@permabond.com

# 1.4. Emergency telephone number

Emergency telephone CHEMTREC UK: +(44)-870-8200418 CHEMTREC US: 800-424-9300 (CCN: 829878)

National emergency telephone CHEMTREC Ireland: +(353)-19014670 number CHEMTREC Australia: +(61)-290372994

CHEMTREC New Zealand: +(64)-98010034

# SECTION 2: Hazards identification

## 2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317

Environmental hazards Not Classified

#### 2.2. Label elements

# **Pictogram**



Signal word Warning

**Hazard statements** H315 Causes skin irritation.

H319 Causes serious eye irritation. H317 May cause an allergic skin reaction.

#### Permabond ET5145B

**Precautionary statements** P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P302+P352a IF ON SKIN: Wash with plenty of soap and water

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

Contains POLYAMIDOAMINE, AMINES, POLYETHYLENEPOLY-, TETRAETHYLENEPENTAMINE

**FRACTION** 

Supplementary precautionary

statements

P264 Wash contaminated skin thoroughly after handling.

P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.

P337+P313 If eye irritation persists: Get medical advice/ attention. P362+P364 Take off contaminated clothing and wash it before reuse.

P501 Dispose of contents/container in accordance with existing Community, National and

local regulations.

## 2.3. Other hazards

None under normal conditions. This substance is not classified as PBT or vPvB according to current EU criteria.

#### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

POLYAMIDOAMINE 30-60%

CAS number: 68082-29-1 EC number: 500-191-5

REACH registration exemption - POLYMER

#### Classification

Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317

#### AMINES, POLYETHYLENEPOLY-,

TETRAETHYLENEPENTAMINE FRACTION

REACH registration number: 01-

1-5%

2119487290-37-XXXX

# Classification

Acute Tox. 4 - H302 Acute Tox. 4 - H312 Skin Corr. 1B - H314 Skin Sens. 1 - H317 Aquatic Chronic 2 - H411

The full text for all hazard statements is displayed in Section 16.

#### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

**Inhalation** Move the exposed person to fresh air. Get medical attention if any discomfort continues.

**Ingestion** Never give anything by mouth to an unconscious person. Do not induce vomiting. Rinse

mouth thoroughly with water. Give plenty of water to drink. Get medical attention if any

discomfort continues.

Skin contact Remove contaminated clothing. Wash skin thoroughly with soap and water. If symptoms

develop, obtain medical attention

#### Permabond ET5145B

Eye contact Remove any contact lenses and open eyelids wide apart. Promptly wash eyes with plenty of

water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention

if any discomfort continues.

## 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact** Skin irritation. Mild dermatitis, allergic skin rash.

**Eye contact** May cause severe eye irritation.

## 4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations. If in doubt, get medical attention promptly. Treat

symptomatically.

# SECTION 5: Firefighting measures

## 5.1. Extinguishing media

**Suitable extinguishing media** Extinguish with foam, carbon dioxide, dry powder or water fog.

Unsuitable extinguishing

media

products

Do not use water jet as an extinguisher, as this will spread the fire.

# 5.2. Special hazards arising from the substance or mixture

**Specific hazards** No unusual fire or explosion hazards noted.

Hazardous combustion

Burning produces irritating, toxic and obnoxious fumes. Nitrous gases (NOx). Carbon

monoxide, carbon dioxide, and unknown hydrocarbons.

#### 5.3. Advice for firefighters

Special protective equipment

for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective

clothing.

# SECTION 6: Accidental release measures

# 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet.

#### 6.2. Environmental precautions

**Environmental precautions** Do not discharge into drains or watercourses or onto the ground.

# 6.3. Methods and material for containment and cleaning up

Methods for cleaning up

Absorb spillage with sand or other inert absorbent. Transfer to suitable, labelled containers for

disposal. Wash area with soap and water.

## 6.4. Reference to other sections

**Reference to other sections** For personal protection, see Section 8. For waste disposal, see section 13.

#### SECTION 7: Handling and storage

## 7.1. Precautions for safe handling

**Usage precautions**Avoid contact with skin and eyes. Do not ingest or inhale. Do not eat, drink or smoke when

using this product. Wash hands thoroughly after handling.

# 7.2. Conditions for safe storage, including any incompatibilities

**Storage precautions** Store in closed original container at temperatures between 5°C and 25°C.

#### 7.3. Specific end use(s)

Specific end use(s) Adhesive. Sealant.

#### Permabond ET5145B

#### SECTION 8: Exposure controls/Personal protection

# 8.1. Control parameters

# POLYAMIDOAMINE (CAS: 68082-29-1)

**DNEL** Workers - Inhalation; Long term systemic effects: 3.9 mg/m³

Workers - Dermal; Long term systemic effects: 1.1 mg/kg/day

PNEC Fresh water; 0.004 mg/l

marine water; 0 mg/l STP; 3.84 mg/l

Sediment (Freshwater); 434.02 mg/kg Sediment (Marinewater); 43.4 mg/kg

# AMINES, POLYETHYLENEPOLY-, TETRAETHYLENEPENTAMINE FRACTION (CAS: 90640-66-7)

**DNEL** Workers - Inhalation; Long term systemic effects: 1.29 mg/m³

Workers - Inhalation; Short term systemic effects: 6940 mg/m³ Workers - Dermal; Long term systemic effects: 0.74 mg/kg/day

Workers - Dermal; Long term local effects: 36 µg/cm2

PNEC Fresh water; 0.0068 mg/l

marine water; 0.0068 mg/l

Sediment (Freshwater); 3.43 mg/kg

STP; 9.73 mg/l

## 8.2. Exposure controls

## Protective equipment







Appropriate engineering controls

Provide adequate general and local exhaust ventilation.

Eye/face protection

The following protection should be worn: Chemical splash goggles or face shield. Personal eye protection should conform to EN 166

Hand protection

It is recommended that chemical-resistant, impervious gloves are worn. Gloves should conform to EN 374. For exposure up to 4 hours, wear gloves made of the following material: Nitrile rubber. Thickness: ≥ 0.4 mm The selected gloves should have a breakthrough time of at least 0.5 hours. For exposure up to 8 hours, wear gloves made of the following material: Nitrile rubber. Thickness: ≥ 0.4 mm The selected gloves should have a breakthrough time of at least 8 hours. The breakthrough time for any glove material may be different for different glove manufacturers. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected.

Other skin and body

protection

Hygiene measures

Employee must wear appropriate protective clothing and equipment to prevent any possibility of skin contact with this substance.

Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

#### Permabond ET5145B

Respiratory protection Ensure adequate ventilation of the working area. Respiratory protection may be required if

excessive airborne contamination occurs. Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible.

Organic vapour filter. Type A. (EN14387)

# SECTION 9: Physical and chemical properties

## 9.1. Information on basic physical and chemical properties

**Appearance** Viscous liquid.

Colour Ivory
Odour Amine.

Odour threshold
 PH
 Mot determined.
 Melting point
 Not determined.
 Initial boiling point and range
 Not determined.

Flash point >100°C

**Evaporation rate** Not available.

Upper/lower flammability or

explosive limits

Not available.

Vapour pressure Not determined.

Vapour density Not determined.

Relative density 1.3

**Solubility(ies)** Insoluble in water. Soluble in the following materials: Organic solvents.

Partition coefficient Not available.

Auto-ignition temperature Not determined.

Decomposition Temperature Not determined.

Viscosity ≈325000 mPa s @ 23°C Thixotropic

Explosive properties Not determined.

Oxidising properties Not applicable.

9.2. Other information

Other information Not relevant.

## SECTION 10: Stability and reactivity

## 10.1. Reactivity

**Reactivity** Under normal conditions of storage and use, no hazardous reactions will occur.

10.2. Chemical stability

**Stability** Stable at normal ambient temperatures.

# 10.3. Possibility of hazardous reactions

Possibility of hazardous

reactions

Reactions with the following materials may generate heat: Epoxy resin

#### Permabond ET5145B

10.4. Conditions to avoid

Conditions to avoid Avoid excessive heat for prolonged periods of time.

10.5. Incompatible materials

Materials to avoid Avoid contact with the following materials: Acids. Oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition

Thermal decomposition could produce carbon monoxide, carbon dioxide, and unidentified

**products** organic compounds.

# SECTION 11: Toxicological information

# 11.1. Information on toxicological effects

**Toxicological effects**The mixture is classified based on the available hazard information for the ingredients as

defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation 1272/2008/EC. Relevant available health/ecological information for the

substances listed under Section 3 is provided in the following.

Aspiration hazard

**Aspiration hazard** None under normal conditions.

**Inhalation** Unlikely to be hazardous by inhalation because of the low vapour pressure of the product at

ambient temperature. Gas or vapour in high concentrations may irritate the respiratory system. Symptoms following overexposure may include the following: Coughing.

**Ingestion**No harmful effects expected from quantities likely to be ingested by accident.

**Skin contact** Irritating to skin. May cause sensitisation by skin contact.

**Eye contact** Irritating and may cause redness and pain.

Toxicological information on ingredients.

#### **POLYAMIDOAMINE**

Acute toxicity - oral

Acute toxicity oral (LD<sub>50</sub> 2,000.1

mg/kg)

Species Rat

Acute toxicity - dermal

Acute toxicity dermal (LD<sub>50</sub> 2,000.1

mg/kg)

Species Rat

Skin corrosion/irritation

**Skin corrosion/irritation** Irritating to skin.

Serious eye damage/irritation

Serious eye Irritating to eyes.

damage/irritation

Respiratory sensitisation

Respiratory sensitisation No information available.

# Permabond ET5145B

Skin sensitisation

Skin sensitisation Sensitising.

Germ cell mutagenicity

**Genotoxicity - in vitro**No information available.

Carcinogenicity

**Carcinogenicity** No specific test data are available.

Reproductive toxicity

Reproductive toxicity -

Screening - NOAEL 1000 mg/kg/day, Oral, Rat

fertility

Specific target organ toxicity - single exposure

**STOT - single exposure** No information available.

Specific target organ toxicity - repeated exposure

**STOT - repeated exposure** No information available.

Aspiration hazard

Aspiration hazard Not available.

# AMINES, POLYETHYLENEPOLY-, TETRAETHYLENEPENTAMINE FRACTION

Acute toxicity - oral

Acute toxicity oral (LD<sub>50</sub> 2,140.0

mg/kg)

Species Rat

Acute toxicity - dermal

Acute toxicity dermal (LD<sub>50</sub> 1,260.0

mg/kg)

Species Rabbit

Acute toxicity - inhalation

Notes (inhalation LC50) No information available.

Skin corrosion/irritation

Skin corrosion/irritation Read-across data. Corrosive

Serious eye damage/irritation

Serious eye Read-across data. Severe irritation.

damage/irritation
Skin sensitisation

**Skin sensitisation** Buehler test - Guinea pig: Sensitising.

Germ cell mutagenicity

**Genotoxicity - in vitro** Read-across data. Gene mutation: Positive.

**Genotoxicity - in vivo** Read-across data. Chromosome aberration: Negative.

Carcinogenicity

Carcinogenicity Read-across data. No evidence of carcinogenicity in animal studies.

#### Permabond ET5145B

Reproductive toxicity

Reproductive toxicity -

No information available.

fertility

Reproductive toxicity -

Read-across data. Developmental toxicity: - NOAEL: >750 mg/kg/day, Oral, Rat

development

Specific target organ toxicity - single exposure

**STOT - single exposure** No information available.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure No information available.

**Aspiration hazard** 

Aspiration hazard Not available.

# SECTION 12: Ecological information

**Ecotoxicity** The product is not expected to be hazardous to the environment.

12.1. Toxicity

**Toxicity**The mixture is classified based on the available hazard information for the ingredients as

defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation 1272/2008/EC. Relevant available health/ecological information for the

substances listed under Section 3 is provided in the following.

#### Ecological information on ingredients.

# POLYAMIDOAMINE

Acute aquatic toxicity

Acute toxicity - fish LC<sub>50</sub>, 96 hours: 7.07 mg/l, Danio rerio (Zebrafish)

Acute toxicity - aquatic

invertebrates

EC₅o, 24 hours: 9.72 mg/l, Daphnia magna

Acute toxicity - aquatic

plants

EC₅o, 72 hours: 4.34 mg/l, Pseudokirchneriella subcapitata

Acute toxicity -

EC₅o, 3 hours: 384 mg/l, Activated sludge

microorganisms

# AMINES, POLYETHYLENEPOLY-, TETRAETHYLENEPENTAMINE FRACTION

Acute aquatic toxicity

Acute toxicity - fish LC<sub>50</sub>, 96 hours: 420 mg/l, Poecilia reticulata (Guppy)

Acute toxicity - aquatic

invertebrates

EC<sub>50</sub>, 48 hours: 24.1 mg/l, Daphnia magna

Acute toxicity - aquatic

plants

EC<sub>50</sub>, 72 hours: 6.8 mg/l, Pseudokirchneriella subcapitata

# 12.2. Persistence and degradability

Persistence and degradability There are no data on the degradability of this product.

#### 12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

#### Permabond ET5145B

Partition coefficient Not available.

12.4. Mobility in soil

Mobility No data available.

# 12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

assessment

This substance is not classified as PBT or vPvB according to current EU criteria.

12.6. Other adverse effects

Other adverse effects None known.

# **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

General information Waste disposal should be in accordance with existing Community, National and local

regulations Empty containers may contain product residue; follow SDS and label warnings

even after they have been emptied.

**Disposal methods**Do not empty into drains, dispose of this material and its container at hazardous or special

waste collection point.

Waste class 08 04 09\* waste adhesives and sealants containing organic solvents or other dangerous

substances.

# SECTION 14: Transport information

**General** The product is not classified as dangerous for carriage.

# 14.1. UN number

Not applicable.

# 14.2. UN proper shipping name

Not applicable.

# 14.3. Transport hazard class(es)

Not applicable.

# 14.4. Packing group

Not applicable.

# 14.5. Environmental hazards

## Environmentally hazardous substance/marine pollutant

No.

# 14.6. Special precautions for user

Not applicable.

# 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

# SECTION 15: Regulatory information

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

# Permabond ET5145B

National regulations The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009

No. 716).

Control of Substances Hazardous to Health Regulations 2002 (as amended).

**EU legislation** Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16

December 2008 on classification, labelling and packaging of substances and mixtures (as

amended).

COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation,

Authorisation and Restriction of Chemicals (REACH)

**Guidance** Workplace Exposure Limits EH40.

Introduction to Local Exhaust Ventilation HS(G)37.

CHIP for everyone HSG228.

Approved Classification and Labelling Guide (Sixth edition) L131.

## 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

#### SECTION 16: Other information

Revision date 17/10/2018

Revision 3

Supersedes date 30/06/2015

Hazard statements in full H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.